



---

## OIL SPOT PRIMER

Oil Spot Primer is a quick drying modified barrier coating, formulated to coat and promote adhesion over oil, grease, and gasoline spots prior to application of asphalt based sealers on asphaltic surfaces. Recommended uses include parking lots, driveways, and any asphaltic surfaces.

### **SURFACE PREPARATION**

Surface areas to be treated must be free from dirt and dust. Scrape excessive build-up of oil, grease, or any chemical stain spots. Lightly burn off excess oil build up.

### **APPLICATION**

Mix well before using. Use full strength on heavy oil spots. Reduce 1 to 1 or 1 to 2 with water, depending on build-up of the oil and grease. Can be applied with suitable spray machine, brushcoater, brush, or roller. Sprinkle a slight amount of silica sand on wet Oil Spot Primer to improve adhesion of asphalt sealer.

When finished, wash tools with water. Use a suitable paint thinner to remove material if it has dried.

### **COVERAGE**

300 to 400 square feet per diluted gallon.

### **CAUTION**

- KEEP FROM FREEZING
- DO NOT STORE IN DIRECT SUNLIGHT
- CONTAINER SHOULD BE CLOSED WHEN NOT USING
- KEEP OUT OF REACH OF CHILDREN

**1-800-953-6490 toll free • [www.specialasphalt.com](http://www.specialasphalt.com)**

**PORTLAND, OR**  
3537 NW Saint Helens Rd  
Portland OR 97210-1313  
Phone: 503.295.6490  
Fax: 503.295.2901

**MEDFORD, OR**  
5758 Crater Lake Ave  
Central Point OR 97502  
Phone: 503.295.6490  
Fax: 503.295.2901

**SPOKANE, WA**  
3117 E Everett Ave  
Spokane WA 99217-6617  
Phone: 509.489.5353  
Fax: 509.489.5408

**SEATTLE, WA**  
9243 M L King Jr Way S  
Seattle WA 98118-5314  
Phone: 206.722.1413  
Fax: 206.725.8626